GNT-SE4020		**Generating Power:** 40W MAX **Generation Voltage:** 16V MAX **Generation Ampere:** 2.5A MAX **Battery Capacity:** 20AH/222 WH **Remaining Battery Display:** 25% Per Grid **Charging Status Display:** Light up the unfilled grids step by step **Charging Voltage:** 9～12.6V **Charging Ampere:** 0～2.5A **Discharge Voltage:** 12.6～9V **Discharge Ampere:** 0～2.5A **Charge & Discharge Protection Ampere:** 10A **Short Circuit Protection Ampere:** 15A **Anti-Overcharge Protection Voltage:** 12.6V **Anti-Over-Discharge Protection Voltage:** 9V **External Power Supply Charging:** 12.6V 2A **Rainy Day Battery Life:** 4～6 days(Connect with Wireless Bridge or Bullet camera or Mini dome camera) **Sunny Day Recharge Time:** Around 1.5 Day **Main Body Bracket Size:** 392 × 244 ×130mm **Solar Panel Size:** 530 × 350 ×17MM* (1pc)

GNT-SE6030		**Generating Power:** 60W MAX **Generation Voltage:** 16V MAX **Generation Ampere:** 3.75A MAX **Battery Capacity:** 30AH/333 WH **Remaining Battery Display:** 25% Per Grid **Charging Status Display:** Light up the unfilled grids step by step **Charging Voltage:** 9～12.6V **Charging Ampere:** 0～3.75A **Discharge Voltage:** 12.6～9V **Discharge Ampere:** 0～2.5A **Charge & Discharge Protection Ampere:** 10A **Short Circuit Protection Ampere:** 15A **Anti-Overcharge Protection Voltage:** 12.6V **Anti-Over-Discharge Protection Voltage:** 9V **External Power Supply Charging:** 12.6V 2A-5A **Rainy Day Battery Life:** 7～6 days(Connect with Wireless Bridge or Bullet camera or Mini dome camera) **Sunny Day Recharge Time:** Around 1.5 Day **Main Body Bracket Size:** 392 × 244 ×130mm **Solar Panel Size:** 530 × 530 ×25MM* (1pc)

GNT-SE8040		**Generating Power:** 80W MAX **Generation Voltage:** 16V MAX **Generation Ampere:** 5A MAX **Battery Capacity:** 40AH/333 WH **Remaining Battery Display:** 25% Per Grid **Charging Status Display:** Light up the unfilled grids step by step **Charging Voltage:** 9～12.6V **Charging Ampere:** 0～5A **Discharge Voltage:** 12.6～9V **Discharge Ampere:** 0～5A **Charge & Discharge Protection Ampere:** 10A **Short Circuit Protection Ampere:** 15A **Anti-Overcharge Protection Voltage:** 12.6V **Anti-Over-Discharge Protection Voltage:** 9V **External Power Supply Charging:** 12.6V 2A-5A **Rainy Day Battery Life:** 4～6 days(Connect with Wireless Bridge or Bullet camera or Mini dome camera) **Sunny Day Recharge Time:** Around 1.5 Day **Main Body Bracket Size:** 572 × 244 ×130mm **Solar Panel Size:** 530 × 350 ×17MM* (2pcs)