reolink	Reolink Innovation Limimted.	
Picture		
Model	**P340**	
Video & Audio	Image Sensor	1/2.49" CMOS Sensor
	Video Resolution	Default: 4512*2512（12Megapixels)@20FPS
	Lens	f=4mm F=1.6, with IR Cut
	Video Format	H.265
	Field of View	Horizontal: 100°
		Vertical: 50°
	Day & Night	IR-cut filter with auto-switching
	Infrared Night Vision	30 Meters(2PCS/1.8W/850nm)
	Color Night Vision	1pcs/4.3W/6500K/700Lumens
	Audio	Two way Audio
Power	POE	IEEE 802.3af, 48V Active
	DC Power	DC 12.0V⎓1A, <12W
Interface	Power	DC power port
	System	Reset Button
	Ethernet	One 10M/100Mbps RJ45
	Storage	MicroSD card slot (Max. 256GB)
	Audio	Built-in Microphone&Speaker
Software Features	Frame Rate	Main Stream: 2fps - 20fps(default: 20fps)
		Sub Stream: 4fps - 15fps(default: 10fps)
	Code Rate	Main Stream: 3072Kbps -10240Kbps(default: 8192Kbps)
		Sub Stream: 128Kbps - 1228Kbps(default: 1024Kbps)
	Browser Supported	Edge, Chrome, Firefox, Safari
	OS Supported	PC: Windows, Mac OS; Smartphone: iOS, Android
	Smart Alarm	Motion Detection/Human Detection/Vehicle Detection/Pet Detection
	Record Mode	Motion Record/Schedule Record (Default: Motion Record)
	Protocols & Standards	HTTPS, SSL, TCP/IP, UDP, HTTP, IPv4, UPnP, RTSP, RTMP, ONVIF, SMTP, NTP, DHCP, DNS,
	Maximal User Access	20 Users (1 admin account & 19 user accounts); Support up to 12 simultaneous video streams (10
	Work with	Google Assistant，Reolink NVR
Working Environment	Temperature	Operating Temperature: -10°C~+55°C (14°F~131°F)
	Humidity	Operating Humidity: 10% ~ 90%
	Waterproof	IP 66
Size & Weight	Dimension	68*63*188mm
	Weight	452g
Warranty	Limited Warranty	2-year limited warranty. For support, visit https://support.reolink.com/hc/en-us/