TTE GPRS Simple 4G

GPRS Communication Module



- SMS notifications for system events
- LEDs for indication of the network status, trouble with the connection to the control panel, etc.;

TTE GPRS Simple is a quad -band GPRS module for serial communication to Teletek Electronics Eclipse series panels. The module is used to send alarm messages to monitoring center or end -user. The module is mounted in small plastic box suitable for wall mounting.TTE GPRS Simple can also be used for remote management, programming and monitoring of the security system together with Teletek Electronics panel and the AJAX SP PRO software application.TTE GPRS Simple communication module is certified according the requirements of RED directive and EN60950 -1.

Features

- SMS notifications for system events
- LEDs for indication of the network status, trouble with the connection to the control panel, etc.;
- Remote access trough AJAX WEB and MobileTTE (iOS/Android) application
- Connection with AJAX SP servers via IP or DNS address;
- Main IP and back -up IP for communication with AJAX SP PRO
- SIA over IP reporting to AJAX SP;
- Micro USB port for module configuration;
- SIM interface;
- Optional 2GB micro SD card for voice messages - Voice Reporting and Voice Guiding (arming, disarming);
- Serial communication with ECLIPSE series control panels;
- Jumper for restoring of factory default settings.

Technical Specifications

Current Consumption:	
-Normal operation mode (standby)	50 mA
-Max. consumption	150 mA
Power supply	From the control panel
Phone numbers for events notification	6
Input filtration time	0.5 sec
Input for AC monitoring	9-35 V AC
Operating frequency	800 Band 20/1800 Band 3/ 2100 Band 1/2600 Band 7 MHz
Antenna connector (SMA)	50 ohm
Encryption	AES 128 bits

Last update: 02/2025