Detectors

PIRIN Series



PIRIN DL

- PIR detector with semi-spherical lens
- 71 Detection zones
- Creep zone protection, mechanically enabled/disabled
- 7 sensitivity levels (selectable)
- Built-in EOL resistors selecting the type of zone balancing, set via jumpers
- Suitable for application in high class buildings - bank offices, storehouses, etc.
- Compact and slim design
- GRADE 2, Class II, INCERT certified



PIRIN MW

- Dual Technology (PIR+MW) detector with semi-spherical lens
- Function “Triple Knock” - maximum protection against false alarms
- Sensitive adjustment - MW and PIR
- 71 Detection zones
- Tamper for protection of box opening and anti-tear tamper on the back
- Creep zone protection, mechanically enabled/disabled
- Built-in EOL resistors selecting the type of zone balancing, set via jumpers
- GRADE 2, Class II, INCERT certified



PIRIN MW AM

- Dual Technology (PIR+MW) detector with semi-spherical lens
- AntiMasking and AntiSpray functions
- Function “Triple Knock” - maximum protection against false alarms
- Sensitive adjustment - MW and PIR
- 71 Detection zones
- Tamper for protection of box opening and anti-tear tamper on the back
- Creep zone protection, mechanically enabled/disabled
- Built-in EOL resistors selecting the type of zone balancing, set via jumpers



Mounting Bracket

- Mounting bracket for detectors PIRIN DL, PIRIN MW, PIRIN MW AM
- Suitable for wall and ceiling mounting
- Designed according the requirements of GRADE 3
- Built-in tamper switch against unauthorized dismantling
- Hidden cables inside the bracket body
- Vertical adjustment range: 0°-8° upside; 0°-24° downside (8° step)
- Horizontal adjustment range: 90°