BRAVO System Peripheral Devices

Teletek electronics

BRAVO PIR



- Digital PIR detector
- 90 degrees coverage area in 54 zones
- Operating range up to 15m
- White light immunity - 5200 Lux
- Temperature compensation
- PET 12kg
- Optional bracket for easy installation
- 1x3V/1500mAh, CR123A battery type
- ~ 3 years battery life
- EN50131, GRADE 2, Class II certified

BRAVO FD



- Combined optical-smoke and heat detector
- Class A1/R according EN54-5
- Rate-of-rise heat part
- Optical chamber auto compensation
- 2x3V/1500mAh, CR123A battery type
- ~ 3 years battery life

BRAVO MC

- Magnetic contact detector
- Hardwired zone for connecting a rolling shutter or other wired detector
- 1x3V/1500mAh, CR123A battery type
- ~ 3 years battery life
- EN50131, GRADE 2, Class II certified



BRAVO CURTAIN



- Curtain detector (combined PIR+MW)
- Two-way communication
- Detection range: up to 12m (adjustable)
- Coverage angle:
  - PIR part: 90° vertical, 7.5° horizontal
  - MW part: 80° vertical, 32° horizontal
- LED indication for Low battery and Test mode
- Operating temperature: -20°C to +60°C
- 1x3V, CR123A battery type
- ~ 1 year battery life

BRAVO PIR EXT GJD



- Digital PIR detector
- Coverage angle 10°-70°
- Adjustment: 180° pan, 90° tilt
- 28 zones for each detection element
- White light immunity – 50 kLux
- Operating temperature -20°C to +55°C
- 3x3V, CR123A battery type
- ~ 3 years battery life
- Outdoor installation, IP65

BRAVO FL

- Flood detector
- 1x3V/1500mAh, CR123A battery type
- 3 years battery life



BRAVO SR300



- Piezo outdoor siren
- Acoustic pressure: 110dB/1m
- Bidirectional tamper
- Internal metal cover
- LED flash
- Battery type:
  - Lithium, 2x3V size "D" or 4x3V size "A"
  - Alkaline, 4x1.5V
- ~ 3 years battery life
- Operating temperature:
  - Lithium, -30°C to +65°C
  - Alkaline, -10°C to +40°C
- Optional power supply with adapter 12VDC/1A
- EN50131, GRADE 2, Class II/Class IV certified

BRAVO RC



- 4 button key fob remote control
- Two-way communication
- LED indication for the system status
- Functions: Arm, Disarm, System information
- Additional button with programmable function
- 1x3V/600mAh, CR2450 battery type
- ~ 3 years battery life
- EN50131, GRADE 2, Class II certified

BRAVO RC-41



- 4-button key fob remote control
- One-way communication
- Operation with several BRAVO panels at the same time
- LED indication for enrollment mode
- Functions: Arm, Disarm
- Two buttons with programmable functionality
- 1x3V/190mAh, CR2032 battery type
- ~ 3 years battery life

BRAVO RC-21



- 2-button key fob remote control
- One-way communication
- Operation with several BRAVO panels at the same time
- LED indication for enrollment mode
- Functions: Arm, Disarm
- 1x3V/190mAh, CR2032 battery type
- ~ 3 years battery life

BRAVO RC-11




- 1-button key fob remote control
- One-way communication
- Operation with several BRAVO panels at the same time
- LED indication for enrollment mode
- Functions: Panic alarm
- 1x3V/190mAh, CR2032 battery type
- ~ 3 years battery life

BRAVO Communication Modules



BRAVO PSTN VD

- PSTN Communication module with voice reporting
- Built-in mounting in BRAVO panel
- 2 GB micro SD card
- 4 Phone numbers for sending messages for events to monitoring station (via CID or SIA protocol) or to User (via User protocol)
- Certified to EN50131, GRADE2, Class II, SP1 (Voice protocol), SP2 (Digital protocol)



BRAVO PSTN

- PSTN Communication module
- Built-in mounting in BRAVO panel
- 4 Phone numbers for sending messages for events to monitoring station (via CID or SIA communication protocol) or directly to User (via User communication protocol)



BRAVO MOUT

- Communication module with outputs
- Two operation modes according the application:
  "MOUT" - For connection of external communication devices and connection of a wired siren
  "PGM" - PGM outputs Management via MobileTTE application
- Built-in mounting in BRAVO panel