Density®
INSTANT FOG PROTECTION

Density® Basic




A new « entry level » fog generator for home and shop target. The Density® Basic fog generator is the key to secure your valuables and permises by instantly repelling intruders.
It is a fog system with a small size and high performances.
Low power consumption.
Plastic cover maximize performances for wireless connections.

FOOD ENVIRONMENT AUTHORISED

WARRANTY 1 YEAR

CLOUD INTERFACE READY

BASIC ELECTRONIC BOARD



JUST **3,8 KG**

FEATURES

45 M² — To protect premises from 5 to 45 m².

135 M³ IN 50 S — Fast and dense, this fog generator produce 135 m³ in 50 seconds.

3 M CEILING

COMPATIBILITY

IP — ActiveCloud board for secure connection (2x128bits encryption) wired or WiFi.

API — API available for software and hardware customisation.

Density Basic technical specifications

GENERAL SPECIFICATIONS

Weight	3,8 kg
Dimensions	325 mm x 265 mm x 115 mm
Color	White
Front cover	Plastic material
Operating time without mains power	1 hour
Heating time	Around 20 minutes
Energy consumption	Around 30 W

FOG GENERATOR

Suggested square meters up to	45 m²
Max fog emitted in single shot	135 m³ (EN standard) - commercial 390 m³
Maximum shooting time	50 sec.
Max fog emitted with full fog bag	2340 m³
N. of shots with max shooting	6
Pump	Yes
Fog tank capacity	500 ml
Horizontal mounting	Yes with opzional kit
Shooting time programmable	Yes
Backup battery	1,2 Ah 12V

INPUTS / OUTPUTS

Electronic board	2 inputs / 3 ouputs

COMMUNICATION

Serial bus with standard protocol	Yes 2 serial
IP card ActiveCloud	Yes (optional)
Access to ActiveCloud	Yes (free)
Availability of Development APIs	Yes
WiFi	Yes (optional antenna)

Accessories for **Density® Basic**

- Orientable wall bracket
- Desk stand
- Active Cloud board
- Wi-Fi antenna for Lan board
- Mounting kit Active Cloud
- Kit for horizontal mounting (side extra riser + fluid bag holder)

Density® refills

- Fluid bag 500 ml **Density® Basic**

Optional configuration

- Demo kit