Loudspeaker with ultra-resistant PP injection-moulded case



## SB-3615

| | |
|---|---|
| CHARACTERISTICS | Loudspeaker with ultra-resistant PP injection-moulded case.<br>Woofer protected by front metal grille.<br>Carrying handles, suspension points, floor supports and monitor-shaped.<br>Hole in the base for 35 mm tube. |
| POWER | 360 W maximum, 180 W RMS |
| LOUDSPEAKERS | 1 x 15" woofer: 63.5 mm coil and ferrite magnet<br>1 compression driver: 1 3/8" diaphragm |
| RESPONSE | 42-18,000 Hz |
| IMPEDANCE | 8 Ohm |
| SENSITIVITY | 98 dB at 1 W/1 m |
| CONNECTORS | 2 x 4-contact loudspeaker connectors (1+, 1-) |
| INDICATORS | Power on the front |
| CROSSOVER | 2 way<br>Crossover frequency at 2,500 Hz |
| SUSPENSION POINTS | 4 M8 points |
| SOUND PRESSURE | 129 dB at maximum power at 1 m |
| DIMENSIONS | 460 x 685 x 380 mm depth |
| WEIGHT | 17.3 KG |


www.fonestar.com | +34 942 254 555 | info@fonestar.es