# DHI-LM24-A200

24" FHD Monitor



**Features**:

· Suitable for continuous 24/7 operation;
· Light and cost-effective plastic housing;
· Ultra-narrow bezel, elegant appearance;
· 178°H/178°V extra-wide viewing angle for overall viewing performance;
· High fidelity digital processing for a brilliant and vivid video;
· Support multiple signal inputs including HDMI and VGA;
· Low energy consumption, long service life;
· Anti-blue light design, eye-protective.




## Technical Specification

### Model

| | |
|---|---|
| Model | DHI-LM24-A200 |

### Display

| | |
|---|---|
| Screen Size | 24" |
| Panel type | VA |
| Aspect Ratio | 16:9 |
| Resolution | 1920×1080 (FHD) |
| Backlight | LED |
| Brightness/Luminance | 220 cd/㎡ |
| Contrast | 3000:1 |
| Display Color | 16.7M(8bit) |
| Viewing Angle(H/V) | 178°(H)/178°(V) |
| Response time(typ.) | 5ms |
| Refresh Rate | TYP. 60Hz, MAX. 75Hz |

### Signals

| | |
|---|---|
| Input | VGA×1, HDMI×1 |

### General

| | |
|---|---|
| Power Supply | DC 12V，2.5A |
| Consumption (Standard) | 30W |
| Consumption (Standby) | ≤0.5W |
| Tilt | -5°~15° |
| Net Weight | 2.79 kg (6.15 lb) |
| Gross Weight | 3.4 kg (7.50 lb) |
| Wall Mount | 100×100mm |
| Dimension without standard (W×H×D) | 542 × 321.3 × 55.3 mm (21.34" × 12.65" × 2.18") |
| Package(W×H×D) | 594 × 123 × 386 mm (23.39" × 4.84" × 15.2") |
| Work Environment | Temperature: 0℃~40℃ (32°F~104°F) |
| | Humidity: 20%~80% |

### Accessory

| | |
|---|---|
| Standard | HDMI cable, power cable, base |
| Optional | Gas spring desk bracket |

### Certifications

| | |
|---|---|
| Certifications | CE/FCC |

Rev 002.000 © 2022 Dahua. All rights reserved. Design and specifications are subject to change without notice.
The images, specifications and information mentioned in the document are only for reference, and might differ from the actual product.