Accessories

Intruder Alarm Systems



GBD 10

- Glass break detector
- Analogue analysis
- Adjustable sensitivity
- Adjustable frequency range
- Sensitive to sounds between 2 and 10kHz



GBD 20

- Glass break detector
- Digital frequency analysis
- Detection of 4 different types of glass
- Pattern recognition technology
- Automatic sensitivity adjustment
- False alarm immunity
- Operating range from 1 to 7 meters
- Coverage area - 180°



GB Tester

- Assists the selection of appropriate place for glass break detector installation
- Two starting modes - automatic and manual
- Four types of glass break tests



AUMS-12S

- Magnetic contacts for door or window use
- Surface mounting with screws of twin adhesive tape
- N/O for closed loop systems
- Contact distance up to 20 - 25mm
- Lead wires length - 400mm



MDU Kit

- Universal remote control module with operating frequency 433MHz
- Transmitting distance 50-100m
- Two independent channels
- Selectable latch or pulse operation mode for each channel
- 2 built-in power relays
- Two remote control units in the set
- Up to 100 remote key fobs



MDU-V

- Remote control module with transmitter
- Rolling code
- One channel
- Up to 15 transmitters
- LED indication for relay output
- 4 programmable operation modes



PS12XX

- Power supply unit
- PS1210 - 12VDC, 1A
- PS1230 - 12VDC, 3A
- Plastic box
- Transformer



PB-U

- Universal plastic box
- Suitable for ECLIPSE ZONE 8 PS, ECLIPSE PGM 8 PS
- Built-in bidirectional tamper switch
- ABS plastic



SB-U

- Suitable for TTE GPRS Standard, TTE GPRS Simple, TTE LAN, TTE Combo, ECLIPSE ZONE8, ECLIPSE PGM8, ECLIPSE WL
- Built-in bidirectional tamper switch
- ABS plastic
- Optional variant with transparent cover