
PA SYSTEM / SPEAKERS / CEILING

GAT-4860SW

100 V LINE TRANSFORMER CEILING SUBWOOFER SPEAKER







- Excellent sound quality
- Bass boost
- Anchorage installation system

ESPECIALLY RECOMMENDED IN:

Hospitality | Retail | Hotels | All sectors

+ Info:
https://fonestar.com/GAT-4860SW

DESCRIPTION

Subwoofer ceiling speakerPerfect for bass reinforcement in installations with musical ambience.It delivers great power with deep bass.ABS built and protective steel grille that guarantees its integrity.Its simple anchor installation system minimises assembly time, with the screws being completely hidden behind the grille.Bass reinforcement for musical ambience of 100 V line installations in shops, bars, restaurants, etc.

TECHNICAL CHARACTERISTICS

FEATURES	Ceiling subwoofer with 100 V line transformer and low profile frameless grille. Bass reinforcement in 100 V line installations.
POWER	90 W maximum, 60 W RMS
LOUDSPEAKERS	1 x 8" woofer
RESPONSE	55-200 Hz (-10 dB)
IMPEDANCE	60 W RMS@100V (166 Ohm) 40 W RMS@100V (250 Ohm) 20 W RMS@100V (500 Ohm)
SENSITIVITY	90 dB at 1 W/1 m
CROSSOVER	Low pass filter, 12 dB/oct.
MATERIAL	ABS and steel grille
COLOUR	White (RAL 9003)
DIMENSIONS	281 mm Ø x 110 mm depth
HOLE	242 mm Ø
WEIGHT	2.7 kg
	Installation system with catches

+ Info:
https://fonestar.com/GAT-4860SW