CAT6 Patch Panel

24-port CAT6 FTP Patch Panel 1U

Specification:

- With CAT6 keystone modules, for 19"cabinet
- Complete metalation and reed construction.
- Modularization design
- Anti-burn performance, meeting the International standard
- Label: Clear label to ensure management
- Designed by international ISO/IEC11801 and TIA/EIA5688.2



Product name	19'' CAT6 FTP Patch panel
Shielded	Yes
Port	24-port
Unit	1U
Material	- Front Panel:1.5mm Metallic panel with plastic powder cladding - Bottom panel: 1.5mm Metallic panel with zinc cladding - Upper cover: 1.0mm Metallic panel with zinc cladding - RJ45 Jack: Housing-fireproof PBT UL-94V0 Pin-8P8C 3u'' gold plating - PCB: 1.6mm UL-94V0/With coded printing T568A/B - IDC body: Fiber-proof PC/ABS UL94V0 - IDC Pin: Phosphor Bronze & Tinned - IDC Terminal: For 22-24 AWG Cable
ELECTRICAL	- VOLTAGE RATING: 125V AC RMS - CURRENT RATING: 1.5A mp - CONTACT RESISTANCE: 100 MILLI OHMS MAX - INSULATION RESISTANCE: 1000M OHMS MIN@500VDC - DIELECTRIC STRENGTH: 750V AC RMS 6OHz, 1MIN - CAT.6 PERMANENT LINK: CONFORM TO ANSI/TIA/EIA-568B.2-1 ISO/IEC 11801:2002 CLASS E
MECHANICAL	- SHIELD MATERIAL: BRASS C680 T=0.25MM - HOUSING MATERIAL: PBT+15%GF UL94V0 - CONTACT MATERIAL: PHOSHOR BRONZE PLATING GOLD - PANEL FRAME: ZN PLATING - IDC MATERIAL:PC UL94VO TERMINAL:PHOSPHOR BRONZE,TIN PLATING - RJ45 JACK LIFE:750 TIMES MIN - IDN LIFE :200 TIMES MIN - RETENTIVENESS OF INSERTION STRUCTURE:50N 60±5s
Operating temperature	-40~+70 ° C

CAT6 Patch Panel

24-port CAT6 FTP Patch Panel 1U





