PUBLIC ADDRESS / SPEAKERS / HORN SPEAKERS

VULKAN-30

LOW IMPEDANCE EXPONENTIAL SPEAKER



IP66

- High efficiency in transmitting messages or warnings
- Long reach
- For outdoor use
- IP-66 protection against dust and water

+ Info:
https://fonestar.com/VULKAN-30

ESPECIALLY RECOMMENDED IN:



Factories



Sports facilities



Hotels



Transport Stations

DESCRIPTION

Exponential speaker. 30 W RMS@8Ohm. IP-66.


TECHNICAL CHARACTERISTICS

FEATURES	Low impedance horn loudspeaker. Prepared for outdoor use with anti-corrosion materials. Protection against water. For long-range message playback.
POWER	30 W RMS
LOUDSPEAKERS	1 compression driver
RESPONSE	400-6,000 Hz (-10 dB)
IMPEDANCE	8 Ohm
SENSITIVITY	105 dB @ 1 W/1 m
MAXIMUM SOUND PRESSURE	118 dB @ 15 W/1 m
DISPERSION	H/V: 180°/160°@500Hz, 90°/80°@1kHz, 50°/40°@2kHz, 40°/30°@4kHz (-6 dB)
PROTECTIONS	IP-66 in compliance with EN 60529
MATERIAL	Diffuser and ABS rear cover with high resistance to sun exposure Aluminium mount Stainless steel screws A2
CONNECTION	30 cm cable with stripped ends
TEMPERATURE RANGE	Operation: -25°C ~ +55°C Storage: -40°C ~ +70°C
HUMIDITY	<95%
COLOUR	Grey (RAL 7035)
DIMENSIONS	285 x 205 x 285 mm depth
WEIGHT	1.7 kg




+ Info:
https://fonestar.com/VULKAN-30

Freq vs Response



Ecala: -:---	A4	Proyecto:	
VULKAN-30 Frequency-Response		Código:	
Autor:		Fecha: 2023-10-02	
Revisado: --		Fecha Revisión: --/--/----	

FONESTAR
Polígono de Trascueto s/n
39600 Revilla de Camargo
Tel: +34 942 254 555
Fax: +34 942 262 777
Web: www.fonestar.es




Map

39: PolarConv F= 500
41: PolarConv F= 1K
43: PolarConv F= 2K
45: PolarConv F= 4K
47: PolarConv F= 8K


Ecala: -:---	A4	Proyecto:	
VULKAN-30 Polar-Diagram		Código:	
Autor:		Fecha: 2023-10-02	
Revisado: --		Fecha Revisión: --/--/----	


FONESTAR
Polígono de Trascueto s/n
39600 Revilla de Camargo
Tel: +34 942 254 555
Fax: +34 942 262 777
Web: www.fonestar.es





Ecala: -:---	A4	Proyecto:	
VULKAN-30 Electric Schema-Diagram		Código:	
Autor:		Fecha: 2023-10-19	
Revisado: --		Fecha Revisión: --/--/----	

FONESTAR
Polígono de Trascueto s/n
39600 Revilla de Camargo
Tel: +34 942 254 555
Fax: +34 942 262 777
Web: www.fonestar.es









FONESTAR	Model	Description	Units	Scale
	VULKAN-30	LOW IMPEDANCE EXPONENTIAL SPEAKER	mm	1:3