



Store

Products

Support

Installation

Partner



1 Lens

2 Status LED

3 Built-in PIR sensor

4 Daylight sensor

5 Built-in microphone

KEEN Ranger PT

Recommended Carriers

Video & Audio



[Store](#)

[Products](#)

[Support](#)

[Installation](#)

[Partner](#)



Interface

Power Port

USB Type-C port

SD Card Slot

Supports Max. 128GB microSD card

SIM card slot

Nano

Reset Button

YES

Audio In/Out

Built-in microphone and speaker

Other Feature(s)

Smart Alarm

PIR detection; person detection; vehicle detection; animal detection; animal recognition(buck/antlerless deer/turkey only)

PIR Detecting Distance

[Store](#)[Products](#)[Support](#)[Installation](#)[Partner](#)

Triggered recording (video/picture/video & picture)

Time Lapse

YES

Smart Home Compatibility

Google Assistant

Cloud Storage

Supports Reolink Cloud (available in selected countries)

3G/4G Bandwidth

Frequency Bands

- Europe: LTE FDD: B1/B3/B7/B8/B28A WCDMA: B1/B8 • America: LTE FDD: B2/B4/B5/B12/B13/B14/B66/B71 • Australia: LTE FDD: B1/B3/B5/B7/B8/B28 WCDMA: B1/B5/B8

Pan & Tilt

PT Angle(Max.)

Pan: 355°, Tilt: 140°

Preset Points

Supports 1 guard position & up to 64 preset positions



[Store](#)

[Products](#)

[Support](#)

[Installation](#)

[Partner](#)



Protocols & Standards

SSL, TCP/IP, UDP, UPNP, SMTP, NTP, P2P

User Access

Max. 12 simultaneous streams (2 main & 10 sub streams)

Power

Battery

6000mAh rechargeable battery (Battery life varies based on settings, usage & temperature.)

Solar

Reolink Solar Panel 2 (6W)

Mechanical

Dimensions

Ø98*122mm

Weight (Battery Included)

496g

Related products