
DHL49

49'' Full-HD LCD Monitor



Features:

· Industrial level DID LCD panel, suitable for extensive 7×24 continuous works
· High fidelity digital processing, brilliant and vivid video
· Built-in 3D COMB filter and 3D Noise Reduction
· Abundant interfaces HDMI, DVI, VGA, BNC, support video loop
· Brightness smart detection, power-saving
· Using Tamper-proof metal housing, no radiation
· Built-in power, low energy consumption, ultra-quiet



Technical Specification

Model		
Model	DHL49	
System		
Diagonal	49"(16:9)	
Resolution	1920×1080 (FHD)	
Backlight	LED	
Brightness/Luminance (Standard)	450 cd/㎡	
Contrast	1100:1	
Angle of view	178°/178°(vertical/horizontal)	
Response time	5.8ms	
Signals		
Input	standard	CVBS(BNC)×2, VGA(D-Sub)×1, DVI-D×1, HDMI×1, RS232×1, USB×1
	optional	Audio×1, RJ45×1, HDCVI×1, SDI×1, DP×1
Output	Standard	CVBS(BNC)×2, RS232×1
	optional	Audio×1, DP×1
General		
Consumption (Standard)	60W	
Consumption (Standby)	≤1W	

Power Supply	AC100~240V (+/-10%),50/60 Hz
Weight	15kg
Dimensions(no base)	1127.1×667.3×52.9mm
Work Environment	Temperature:0℃~50℃
	Humidity:20%~90%
Accessory	
Standard	VGA cable, power cable
Optional	Pedestal,hanging bracket

Dimensions(mm)

