ACCESSORIES

FIRE ALARM SYSTEMS



FRL - 1

- Remote 24V fire indicator
- Repeats the status of 1 or several fire detectors (up to 3 SensoMAG or SensoIRIS detectors)
- 1 input
- Complies with EN54-23



DeepBase W

- Deep base accessory
- Color - white (RAL 9016)
- Application for mounting on rough surfaces, pipelines, floating ceilings, etc
- Compatible with SensoMAG detectors, SensoIRIS detectors, SensoIRIS WSxx abd BSxx sounders, SF100 WSST sounder




DeepBase R

- Deep base accessory
- Color - red (RAL 3020)
- Application for mounting on rough surfaces, pipelines, floating ceilings, etc
- Compatible with SensoIRIS WSxx sounders, SF100 RSST/RSND sounders



Fireray One

- Reflective smoke beam detector
- Auto-alignment protocol
- Operating voltage: 14 - 36VDC
- Operating current: 5mA
- Low current consumption
- Signal output: Individual Alarm and Fault relays (VFCO) 2A @ 30 VDC
- Operating distance: 5 -120m (for 5-50m - one reflector is required; for 50-120m - 4 reflectors are required)
- Suitable for installation into large and small places
- IP55
- Certified to EN54-12



FLM Kit

- Kit for flush mounting
- For use on 25 mm thick dry wall
- Includes: 2 hangers, mounting screws
- Compatible with IRIS and MAG8Plus



PS2410

- Power supply unit
- 24 VDC/1A
- Metal box
- Transformer
- Complies with EN54-4



SB-U

- Universal small plastic box
- For application with ML log memory module in installation with MAG8 fire alarm panel
- Transparent cover for easy visual inspection