MOUNTS / DYNAMIC MICROPHONES / CABLES

ELIPSE-8T

NETO: 0,00

PAREJA DE ALTAVOCES DE SUPERFICIE CON TRANSFORMADOR DE LíNEA DE 100 V Y BAJA IMPEDANCIA



DESCRIPTION

Pair of low impedance loudspeakers with 100 V line transformer. Specially designed for PA and background applications; a solution for installations in public areas such as restaurants, cafeterias, supermarkets, shopping centres, etc.
Excellent finish, stylish design, high power and resistant.
Adjustable wall mount can be swivelled in all directions for easy installation.

TECHNICAL CHARACTERISTICS

FEATURES	Pair of low impedance loudspeakers with 100 V line transformer. Designed for outdoor use, water-resistant and rustproof materials.

Expand product information on:
https://fonestar.com/es/ELIPSE-8T

POWER	120 W maximum, 60 W RMS
LOUDSPEAKERS	1 x 8" polypropylene woofer 1 x 1" silk dome tweeter
RESPONSE	30-20,000 Hz
IMPEDANCE	High Z 100 V line: 200 Ohm (50 W) 400 Ohm (25 W) 800 Ohm (12.5 W) 1,600 Ohm (6.25 W) Low Z: 8 Ohm
SENSITIVITY	90 dB at 1 W/1 m
SWITCH	W selector in high Z and low Z
PROTECTION	IP-56
MATERIALS	Aluminium grille Weatherproof mount Stainless steel screws
CONNECTORS	Spring terminals
COLOUR	Black (RAL 9017)
DIMENSIONS	244 x 378 x 240 mm depth
WEIGHT	2 x 5 kg
ACCESSORIES	Adjustable fixing mounts

Expand product information on:
https://fonestar.com/es/ELIPSE-8T