Eclipse LED 16A
LED Keypad

EN 50131
GRADE 2 Class II

Description

LED 16A is a keypad with LED indication of zones, system troubles, alarm messages and arming type. It is part of the ECLIPSE series alarm systems. The keyboard provides 1 input zone. LED 16 is suitable for programming and management of systems with up to 3 independent areas and up to 16 zones.



Technical Specifications

Power Supply from the control panel	9-18V (nom. 14V)
Consumption	Min. 50mA / Max. 80mA
Area Indication	3
Zone Indication	16
Panic buttons	Yes
Buttons	Rubber
Operation temperature	-20 to +50°C
Tamper	Yes
Dimensions	100x90x24mm

Functional Specifications

- Shortcut buttons to additional menus – Memory, Troubles display and Bypassed zones;
- Quick buttons for all arming modes;
- 3 fast buttons' combination for sending of PANIC, MEDICAL and FIRE alarm messages to a central monitoring station;
- The system parameters can be fully programmed;
- Supports 2 programming types: 4-digit addresses and 3-digit operations;
- Adjustable intensity of backlight for the display and buttons;
- Adjustable sound volume of the internal buzzer.

Packing Information

- **Master box** - 80 units LED 16A, dimensions 496 x 305 x 206 mm

Compatible Product Range

- **Eclipse 8** - Alarm Control Panel
- **Eclipse 16** - Alarm Control Panel
- **Eclipse 32** - Alarm Control Panel

Contact Information

Teletek Electronics JSC
14A Srebarna Str, 1407 Sofia, Bulgaria
Tel.:+359 2 9694 800
Fax: +359 2 9625 213
info@teletek-electronics.bg
www.teletek-electronics.com