

 Reolink Innovation Limited		
Picture		
Model	TrackMix Series P760	
Video & Audio	Image Sensor	1/3"+1/2.8"CMOS Sensor
	Video Resolution	UP To: 3840 x 2160 (8.0 Megapixels) at 25 frames/sec
	Lens	f=2.8mm@F=1.6, f=8mm@F=1.6
	Video Format	H.264,H.265
	Field of View	Horizontal: 104°-38° Vertical: 60°-21°
	Zoom Mode	6X hybrid zoom
	Day & Night	IR-cut filter with auto-switching
	Infrared Night Vision	Up to 30 Meters (100ft)(LED: 2pcs/850nm)
	Color Night Vision	Spotlight: 2pcs/6500K/450 Lumens
	Audio	Two-way Audio
Power	POE	IEEE 802.3af, 48V Active
	DC Power	DC 12.0V=2A, <12W
Interface	Power	DC power port
	System	Reset Button
	Ethernet	One 10M/100Mbps RJ45
	Storage	MicroSD card slot (Max. 256GB)
	Audio	Built-in Microphone and Speaker
Pan&Tilt	Pan &Tilt Range	Pan: 355°, Tilt: 0°~90°
	Pan Speed	2.5°-90°/s (Speed can be set)
	Tilt Speed	1.5°-60°/s (Speed can be set)
	Preset	64
	Auto Tracking	Support
Software Features	Frame Rate	Main Stream: 2fps - 25fps Sub Stream: 4fps - 20fps
	Code Rate	Main Stream: 4096Kbps -8192Kbps Sub Stream: 128Kbps -1228Kbps
	Browser Supported	Edge, Chrome, Firefox, Safari
	OS Supported	PC: Windows, Mac OS; Smartphone: iOS, Android
	Smart Alarm	Motion detection/Human Detection/Vehicle Detection/Pet Detection
	Record Mode	Motion Record/Schedule Record (Default: Motion Record)
	Protocols & Standards	HTTPS, SSL, TCP/IP, UDP, HTTP, IPv4, UPnP, RTSP, RTMP, ONVIF, SMTP, NTP, DHCP, DNS, DDNS,
	Maximal User Access	Support up to 12 simultaneous video streams (10 substreams & 2 mainstreams)
	Work with	Google Assistant,Reolink NVR
Working Environment	Temperature	Operating Temperature: -10°C~+55°C (14°F~131°F)
	Humidity	Operating Humidity: 10% ~ 90%
	Waterproof	Support
Size & Weight	Dimension	228.2*147*129mm
	Weight	1.21KG
Warranty	Limited Warranty	2-year limited warranty. For support, visit https://support.reolink.com/hc/en-us/